

KEMCO Decor Stone / Natural Stones

Application area

- For the decorative design/finish of the different surfacing systems for balconies, terraces, walls and floors
- · For new buildings and repair work

Features

- · Mechanically rounded, natural appearance
- · Washed and dried
- Grading curve 2 4 mm

Pack sizes

25 kg bag

Storage

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

Allow the material to stabilize to between +18°C and +20°C for at least 24 hours prior to use.

Properties

Weight

approx. 2.50 g/cm³, bulk weight 1.7 t/m³

Colors

- · contrast black
- light gray
- dark beige
- contrast brown
- copper / beige
- · light brown / terra
- anthracite
- chestnut

other colors on request.

Application

To avoid colour variations or shading over the surface, material from different bags must be mixed in advance.

Important note

Please refer to the respective safety data sheet for hazard warnings, protective measures, hazardous substance classes and correct disposal!

Disposal

EAK 17 05 04

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEM-PER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30

Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.