

KEMCO NQ 0408 Natural Quartz

Application area

- · For new buildings and repair work
- Depending on the application of the respective COELAN products
- · Indoor and outdoor use

Features

- Kiln-dried
- Grading curve that is adapted to the intended purpose and compatible with the system

Pack sizes

25 kg bag

Storage

Cool and dry.

Properties

Form

	depending on the weather conditions, such as wind, humidity and temperature	
CE marking		
Component to 4		ETA 03/0025
		ETA 03/0026
		ETA 03/0043
		ETA 03/0044
Appli	ication	

Granular /solid

EAK 17 05 04

Disposal

No hazardous waste, disposal as domestic waste.

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition su-

persedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEM-PER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30